

# FULFLO DE CARTRIDGE FILTERS



# **Fulflo DE**

The secret behind the effectiveness of DE filters is the filter media itself. Water passes through extremely fine, highly porous Diatomaceous Earth (DE) which filters out the finest particles. Diatomaceous earth is a porous powder with microscopic openings, that, when magnified, look like tiny sponges. Clear water can pass through these openings, but particles, as small as one to three microns, are trapped during the first pass through the media. D.E. filters have internal elements that become coated with D.E. It is this 'filter cake' that strains dirt, dust, algae, and some forms of bacteria from the water.

## Construction

Made from specially engineered polymers, the Fulflo DE filter's outer casing is capable of withstanding the highest pressures your pool is likely to provide. It also has a unique and convenient split ring design for easy cleaning.


The heart of the Fulflo DE filter is the septum, comprising 10 polypropylene covered grids. These grids are spaced far enough apart to prevent the DE clogging while still allowing backwashing to be 100% effective.

### **Maintenance**

The long-lasting smooth poly-propylene fabric used in the filters ensures lower start-up pressures and longer filter cycles. DE is renowned for its non-binding properties which help in the backwashing, thus the poly-propylene grids can be rejuvenated even if the filter has been neglected.

# **Warranty**

Fulflo DE Filters are covered by Waterco's comprehensive 5 year (3 + 2) conditional tank warranty, (from date of purchase). All other components carry a one year warranty.



| Model Number                 | P2027  | P2036   | P2048   |
|------------------------------|--------|---------|---------|
| Filter Area (sq m)           | 2.3    | 3.3     | 4.4     |
| Average Flow Rate (Ipm)      | 255    | 360     | 484     |
| Max. Pool Size (litres)      | 92,000 | 130,000 | 174,000 |
| Filter Media (kg)            | 1.50   | 1.75    | 2.15    |
| Dimensions (mm)              |        |         |         |
| Height                       |        |         |         |
| - incl. pressure gauge       | 850    | 1050    | 1250    |
| - to centre of return outlet | 420    | 450     | 650     |
| - to centre of pump outlet   | 480    | 490     | 690     |
| Width                        | 500    | 500     | 500     |
| Depth (including MPV)        | 700    | 800     | 800     |

OFFIGES - AUSTRALIA

NSW - Sydney (Head Office)
Tel: +61 2 9898 8600

QLD - Brisbane
Tel: +61 7 3299 9900

VIC/TAS - Melbourne
Tel: +61 3 9764 1211

Tel: +61 8 9273 1900

Tel: +61 8 8244 6000

SA/NT - Adelaide

Waterco (Europe) Limited Sittingbourne, Kent. UK Tel: +44 (0) 1795 521 733 Waterco (USA) Inc Augusta, Georgia, USA Tel: +1 706 793 7291

Tel: +1 706 793 7291 Waterco Canada Longueuil, Quebec, Canada Tel: +1 450 748 1421 Waterco (NZ) Limited

Auckland, New Zealand

Waterco (C) Limited Guangzhou, China Tel: +86 20 3222 2180 Waterco (Far East) Sdn Bhd Selangor, Malaysia Tel: +60 3 6145 6000 PT Waterco Indonesia Jakarta. Indonesia

Tel: +62 21 4585 1481

Waterco Singapore Intl Pte Ltd

Nehsons Building, Singapore

Waterco France SAINT PRIEST, France Tel: +33 4 72 79 33 30 DISTRIBUTED BY: